

# CHARLES PARSONS

Apparel Fabrics

Est. 1915

## TRIMMINGS

### DATA SHEET

# 1400F FORMFUSE

**DESCRIPTION**

NON WOVEN FUSIBLE INTERLINING

**APPLICATION**

LEIGHTH WEIGHT FUSIBLE. USED FOR SMALL PARTS SUCH AS COLLARS, CUFFS AND PLACKETS. ALSO USED AS AN EMBROIDERY BACKING.

**COLOURS**

WHITE AND CHARCOAL

**WEIGHT**

36 GSM

**WIDTH**

100 CM

**ROLL LENGTH**

50 MTS

**COMPOSITION**

60% POLYESTER, 25% ACRYLIC, 15% RAYON

**COATING**

POLYETHYLENE - LOW DENSITY

**FUSING CONDITIONS**

DIAL TEMP:	130-140°C
GLUELINE TEMP:	120-130°C
PRESSURE:	20-30N/cm   2-3 BAR
TIME:	10-12 SECONDS

**CARE INSTRUCTIONS**

WASHABLE UP TO 40 °C

The information contained in this performance specification sheet is subject to change without notice and remains the property of Charles Parsons and Co. It shall not be reproduced in whole or part, nor provided to any third parties without the written authorisation of Charles Parsons and Co. Charles Parsons and Co makes no warranty of any kind with regard to this technical specification, including but not limited to, the implied warranties of merchantability and fitness for a particular purpose. Charles Parsons and Co shall not be liable for incidental or consequential damages in connection with the supply, performance or use of this fabric. The previous conditions are only a guide. A preliminary trial is recommended before using the product in production

QUOTED BY: \_\_\_\_\_

DATE: \_\_\_\_\_

PRICE: \_\_\_\_\_ GST INC/EXC